



WINNING GCD

coffee machines

WINNING GCD

coffee machines


- Modern design coordinated with Snack & Food models
- Smooth and linear outside surface, easy to clean
- Panels back-lit by low-consumption LEDs, easy to customize
- Selection keypad with touch technology and LEDs-lit keys
- Graphic colour display 480 x 272 pixel with the possibility of personalised slide shows and / or visualization of supplementary information (ex: product ingredients and nutritional value)
- High-performance FAS MF1 flat blade grinding/metering unit
- Facilitated access to the distributor to reduce maintenance times
- Pre-painted machine structure with door with 3 closure points and programmable Rieda lock block
- Ready for anti-vandal coin input kit
- Top and side break-in prevention bars
- 650 cc heater with high-precision temperature probe
- 32 - bit electronics with USB 2.0 HOST
- Rieda RS1 Lock
- Energy saving function
- Programming, cloning, and Audit functions using a standard USB Pen Drive



Winning GCD + Faster GCD 900



Cup dispenser with double hinge joint for complete articulation of the unit, facilitates access to the internal machine parts for all loading, maintenance and cleaning operations



Mixer solenoid valve guarantees instant beverages with optimal differentiated temperatures



Flat blade professional grinder MF1



Available flat blade professional grinder MF2 with automatic grinding variation

E_6					
1	2	3	4	5	6
Sugar (on door)	Tea	Chocolate	Milk	Instant coffee	Coffee beans
3,8 kg	2,7 kg	4,0 kg	1,7 kg	0,8 kg	4,0 kg

E_7						
1	2	3	4	5	6	7
Sugar (on door)	Tea	Chocolate	Milk	Instant coffee 1	Instant coffee 2	Coffee beans
3,8 kg	2,7 kg	4,0 kg	1,7 kg	0,8 kg	1,0 kg	4,0 kg

I_7						
1	2	3	4	5	6	7
Tea	Chocolate	Milk	Instant coffee 1	Sugar	Instant coffee 2	Other instant
2,7 kg	4,0 kg	1,7 kg	0,8 kg	4,8 kg	0,8 kg	3,5 kg

The showing maximum capacity is purely indicative, weight can change depending on products.



versione black

versione silver

General Features

		E_6	E_7	L_7
Height	mm	1830	1830	1830
Width	mm	610	610	610
Depth	mm	690	690	690
Depth with open door	mm	1260	1260	1260
Weight	Kg	160	165	150
Power supply	V / Hz	230 / 50	230 / 50	230 / 50
Power capacity*	W	1560	1560	1800
Water connection	Mpa	0,1 / 0,8	0,1 / 0,8	0,1 / 0,8
Cups (166 cc)	n°	780	780	780
Stirrers	n°	585	585	optional
Canisters	n°	6	7	7
Boiler	cc	pressure boiler 650	pressure boiler 650	instant boiler 1500
Protocol		MDB Executive BDV	MDB Executive BDV	MDB Executive BDV
Direct selection	n°	18	18	18
Pre-selection	n°	2	2	2
Graphical display		LCD 240x128 pixel	LCD 240x128 pixel	LCD 240x128pixel
Standard version		black RAL 9005 & aluminium	black RAL 9005 & aluminium	black RAL 9005 & aluminium
Variant		silver & aluminium	silver & aluminium	silver & aluminium

*An EVA-EMP list indicating the power consumption of the machine is available on request.



Fas International Spa
Via Lago di Vico, 60
36015 Schio - Vicenza - Italy

Tel. +39 0445 502011
Fax +39 0445 502010

info@fas.it
www.fas.it



ISO 14001:2004



UNI EN ISO 9001:2008
N. 9190 FASI



N. IT 8691